

Norit Electronic Version

Datasheet

Food

Norit SA 5 PAH-HF

Norit SA 5 PAH-HF is specially developed for bleaching of edible oils and fats. It is especially suitable for the removal of polycyclic aromatic hydrocarbons (PAH) from vegetable oils. As a result of its composition, hydrolysis of oil is minimized when using this carbon. Norit SA 5 PAH-HF is a steam activated carbon produced under stringent controlled conditions at which equal adsorptive capacities and filtration properties are ensured for every produced lot. Norit SA 5 PAH-HF is developed to provide the optimum balance between required adsorptive capacity and oil retention in the filter cake.

Norit SA 5 PAH-HF meets the requirements of the U.S. Food Chemicals Codex (6th edition, 2008). It is produced under the scope of a Quality Management System which complies with the requirements of CDX HACCP. The corresponding Certificate of Registration is available upon request.

Document No.

SD5HF

Product / Application

Powdered activated carbon

Version

27 April 2009

Norit Nederland BV

Nijverheidsweg-Noord 72
3812 PM Amersfoort
P.O. Box 105
3800 AC Amersfoort
The Netherlands

T: +31 33 46 48 911
F: +31 33 46 17 429
E: sales@norit.com
I: www.norit-ac.com

SPECIFICATIONS

Fluorescent substances	Not detected	-
Light PAH adsorption index	min. 4.0	-
Heavy PAH adsorption index	min. 9.7	-
Moisture (as packed)	max. 7	mass-%
Filtration time	max. 15	min

GENERAL CHARACTERISTICS

Light PAH adsorption index	5.1	-
Heavy PAH adsorption index	10.1	-
Total surface area (B.E.T.)	850	m ² /g
Apparent density (tamped)	550	kg/m ³
Particle size D ₁₀	6	µm
Particle size D ₅₀	35	µm
Particle size D ₉₀	100	µm
Ash content	13	mass-%
Chloride (acid extr.)	0.1	mass-%
pH	alkaline	-
Moisture (as packed)	3	mass-%
Filtration time	11	min


Norit

leading in purification

Activated Carbon

NOTES

- 1 All analyses based on Norit Standard Test Methods (NSTM)
- 2 Specifications are guaranteed values based on lot to lot quality control, as covered by Norit's ISO 9001 certification.
- 3 General characteristics reflect average values of product quality.

PACKAGING

Norit SA 5 PAH-HF is available in:

- Multiply paper bags of 20 kg, 56 bags per pallet, shrink wrapped (1120 kg net weight per pallet)
- Bulk bags of 900 kg net weight on a pallet, shrink wrapped
- Bulk tank cars

Product availabilities depend on the type of packaging.

Caution: For health and safety related aspects please refer to the Material Safety Datasheet (MSDS), which is available on request.

Notes: Any product quality information including specifications given was valid at the time of issuance of the publication. However, we maintain a policy of continuous development and reserve the right to amend any product quality aspects without notice. All data and suggestions regarding the use of our products are believed to be reliable and given in good faith. However, they are given without guarantee, as the use of our products is beyond our control, and are not to be construed as recommendation or instigation to violate any existing patent.

This datasheet is generated in an electronic way and is meant to be used only for the purpose of convenience. In case of divergencies between this datasheet and the original datasheet available at Norit's headoffice, the original datasheet prevails. Customer should notify Norit immediately of this divergence.

This datasheet (Issue 27 April 2009) replaces previous issues.

Norit

leading in purification

Activated Carbon